


# 塑封肖特基二极管

# PLASTIC SCHOTTKY BARRIER RECTIFIER



## 特征 Features

- 大电流承受能力。High Current Capability
- 正向压降低。Low Forward Voltage Drop
- 高温焊接保证 High temperature soldering guaranteed:  
260°C/10 秒, 0.375" (9.5mm)引线长度。  
260°C/10 seconds, 0.375" (9.5mm) lead length,
- 引线可承受5 磅 (2.3kg) 拉力。 5 lbs. (2.3kg) tension
- 引线和管体皆符合RoHS标准。  
Lead and body according with RoHS standard

## 机械数据 Mechanical Data

- 端子: 镀锡轴向引线 Terminals: Plated axial leads
- 极性: 色环端为负极 Polarity: Color band denotes cathode end
- 安装位置: 任意 Mounting Position: Any

**极限值和电参数** TA = 25°C 除非另有规定。

**Maximum Ratings & Electrical Characteristics** Ratings at 25°C ambient temperature unless otherwise specified.

	符号 Symbols	20SQ020	20SQ040	20SQ050	20SQ060	单位 Unit
最大峰值反向电压 Maximum repetitive peak reverse voltage	V <sub>RRM</sub>	20	40	50	60	V
最大反向有效值电压 Maximum RMS voltage	V <sub>R(RMS)</sub>	14	28	35	42	V
最大直流阻断电压 Maximum DC blocking voltage	V <sub>DC</sub>	20	40	50	60	V
最大正向平均整流电流 Maximum average forward rectified current	I <sub>FM</sub>	20				A
最大正向电压降 IF = 20A Maximum forward voltage	V <sub>F</sub>	0.50	0.50	0.70	0.70	V
正向峰值浪涌电流 10mS单一正弦半波 Peak forward surge current 8.3 ms single half sine-wave	I <sub>FSM</sub>	280				A
最大反向漏电流 TA = 25°C Maximum reverse current TA = 100°C	I <sub>R</sub>	0.50 50				mA
典型热阻 Typical thermal resistance	R <sub>θJC</sub>	3.5				°C/W
典型结电容 V <sub>R</sub> = 4.0V, f = 1.0MHz Type junction capacitance	C <sub>j</sub>	450				pF
结温 Junction tempeature Range VR≤80%V <sub>RRM</sub>	T <sub>j</sub>	-55 --- +150 -55 --- +150				°C
工作温度和存储温度 Operating junction and storage temperature range	T <sub>STG</sub>	-55 --- +150				°C

## 特性曲线 Characteristic Curves

