


- 3-Terminal Regulators
- Output Current up to 100 mA
- No External Components
- Internal Thermal-Overload Protection
- Internal Short-Circuit Current Limiting
- Provided Pb-Free packages from the end of 2004

description

This series of fixed-voltage integrated-circuit voltage regulators is designed for a wide range of applications. These applications include on-card regulation for elimination of noise and distribution problems associated with single-point regulation. In addition, they can be used with power-pass elements to make high-current voltage regulators. One of these regulators can deliver up to 100 mA of output current. The internal limiting and thermal-shutdown features of these regulators make them essentially immune to overload. When used as a replacement for a zener diode-resistor combination, an effective improvement in output impedance can be obtained, together with lower bias current.



SOT-89
78L24CPK

electrical characteristics at specified virtual junction temperature, $V_J = 32V$, $I_O = 40mA$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T [‡]	78L24			UNIT
			MIN	TYP	MAX	
Output voltage	$I_O = 1mA$ to $40mA$, $V_J = 26.5$ to $39V$	25°C	23	24	25	V
	$I_O = 1mA$ to $70mA$	Full range	22.8	24	25.2	
Input voltage regulation	$V_J = 26.5V$ to $39V$	25°C	95	480	480	mV
	$V_J = 29V$ to $39V$		78	400	400	
Ripple rejection	$V_J = 27.5V$ to $37.5V$, $f = 120$ Hz	25°C	30	33	33	dB
Output voltage regulation	$I_O = 1mA$ to $100mA$	25°C	41	240	240	mV
	$I_O = 1mA$ to $40mA$		28	120	120	
Output noise voltage	$f = 10$ Hz to 100 kHz	25°C	97	97	97	µV
Dropout voltage		25°C	1.7	1.7	1.7	V
Bias current		25°C	4.8	6.5	6.5	mA
		125°C	6	6	6	
Bias current change	$V_J = 28V$ to $39V$	Full range		1.5	1.5	mA
	$I_O = 1mA$ to $40mA$			0.1	0.1	

78L24


absolute maximum ratings over operating temperature range (unless otherwise noted)

78L24	PARAMETER	UNIT
Input voltage, V_I	40	V
Virtual junction temperature range, T_J	150	°C
Lead temperature 1.6 mm (1/16 inch) from case for 10 seconds	260	°C
Storage temperature range, T_{STG}	-65 to 150	°C

recommended operating conditions

78L24	MIN	MAX	UNIT
Input voltage, V_I	26.5	39	V
Output current, I_O	100		mA
Operating virtual junction temperature, T_J	0	70	°C

Pad Location 78L24



Chip size 1.0 x 1.2 mm

Pad N	Pad Name	X (um)	Y (um)
1	Ground	95	100
2	Input	820	1010
3	Output	535	1015