- **Meets or Exceeds the Requirements of ANSI TIA/EIA-422-B and ITU Recommendation V.11**
- **Operates From a Single 5-V Supply**
- **TTL Compatible**
- **Complementary Outputs**
- **High Output Impedance in Power-Off Conditions**
- **Complementary Output-Enable Inputs**

D OR N PACKAGE
(TOP VIEW)



description

The AM26LS31C is a quadruple complementary-output line driver designed to meet the requirements of ANSI TIA/EIA-422-B and ITU (formerly CCITT) Recommendation V.11. The 3-state outputs have high-current capability for driving balanced lines such as twisted-pair or parallel-wire transmission lines, and they provide a high-impedance state in the power-off condition. The enable function is common to all four drivers and offers the choice of an active-high or active-low enable (G, $\overline{G}$) input. Low-power Schottky circuitry reduces power consumption without sacrificing speed.

The AM26LS31C is characterized for operation from 0°C to 70°C.

FUNCTION TABLE
(each driver)

INPUT A	ENABLES		OUTPUTS	
	G	$\overline{G}$	Y	Z
H	H	X	H	L
L	H	X	L	H
H	X	L	H	L
L	X	L	L	H
X	L	H	Z	Z

H = high level, L = low level, X = irrelevant,
Z = high impedance (off)

schematic (each driver)



All resistor values are nominal.

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)†

Supply voltage, V_{CC} (see Note 1)	7 V
Input voltage, V_I	7 V
Output off-state voltage	5.5 V
Package thermal impedance, θ_{JA} (see Note 2): D package	113°C/W
N package	78°C/W
Storage temperature range, T_{stg}	–65°C to 150°C
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds	260°C

† Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTES: 1. All voltage values, except differential output voltage V_{OD}, are with respect to network GND.
2. The package thermal impedance is calculated in accordance with JESD 51, except for through-hole packages, which use a trace length of zero.

recommended operating conditions (unless otherwise noted)

	MIN	NOM	MAX	UNIT
Supply voltage, V_{CC}	4.75	5	5.25	V
High-level input voltage, V_{IH}	2			V
Low-level input voltage, V_{IL}			0.8	V
High-level output current, I_{OH}			–20	mA
Low-level output current, I_{OL}			20	mA
Operating free-air temperature, T_A	0		70	°C

electrical characteristics over operating free-air temperature range (unless otherwise noted)

PARAMETER		TEST CONDITIONS		MIN	TYP†	MAX	UNIT
V_{IK}	Input clamp voltage	V_{CC} = 4.75 V,	I_I = –18 mA			–1.5	V
V_{OH}	High-level output voltage	V_{CC} = 4.75 V,	I_{OH} = –20 mA	2.5			V
V_{OL}	Low-level output voltage	V_{CC} = 4.75 V,	I_{OL} = 20 mA			0.5	V
I_{OZ}	Off-state (high-impedance-state) output current	V_{CC} = 4.75 V	V_O = 0.5 V			–20	µA
			V_O = 2.5 V			20	
I_I	Input current at maximum input voltage	V_{CC} = 5.25 V,	V_I = 7 V			0.1	mA
I_{IH}	High-level input current	V_{CC} = 5.25 V,	V_I = 2.7 V			20	µA
I_{IL}	Low-level input current	V_{CC} = 5.25 V,	V_I = 0.4 V			–0.36	mA
I_{OS}	Short-circuit output current‡	V_{CC} = 5.25 V		–30		–150	mA
I_{CC}	Supply current	V_{CC} = 5.25 V,	All outputs disabled		32	80	mA

† All typical values are at V_{CC} = 5 V and T_A = 25°C.
‡ Not more than one output should be shorted at a time, and duration of the short circuit should not exceed one second.

switching characteristics, V_{CC} = 5 V, T_A = 25°C (see Figure 1)

PARAMETER		TEST CONDITIONS		MIN	TYP	MAX	UNIT
t_{PLH}	Propagation delay time, low-to-high-level output	C_L = 30 pF,	S1 and S2 open		14	20	ns
t_{PHL}	Propagation delay time, high-to-low-level output				14	20	
t_{PZH}	Output enable time to high level	C_L = 30 pF	R_L = 75 Ω		25	40	ns
t_{PZL}	Output enable time to low level		R_L = 180 Ω		37	45	
t_{PHZ}	Output disable time from high level	C_L = 10 pF,	S1 and S2 closed		21	30	ns
t_{PLZ}	Output disable time from low level				23	35	
	Output-to-output skew	C_L = 30 pF,	S1 and S2 open		1	6	ns