

## HIGH EFFICIENCY ULTRAFAST DIODE

### MAIN PRODUCT CHARACTERISTICS

$I_{F(AV)}$	2 x 4A
$V_{RRM}$	200 V
$T_j$ (max)	175 °C
$V_F$ (max)	0.95 V
$t_{rr}$ (max)	20 ns


### FEATURES AND BENEFITS

- Suited for SMPS
- Low losses
- Low forward and reverse recovery times
- High surge current capability
- High junction temperature
- Insulated package: TO-220FPAB

### DESCRIPTION

Dual center tap rectifier suited for Switch Mode Power Supplies and High frequency DC to DC converters.

Packaged in DPAK, TO-220AB or TO-220FPAB. This device is intended for use in low voltage, high frequency inverters, free wheeling and polarity protection applications.



### ABSOLUTE RATINGS (limiting values)

Symbol	Parameter			Value	Unit	
$V_{RRM}$	Repetitive peak reverse voltage			200	V	
$I_{F(RMS)}$	RMS forward current	TO-220AB / TO-220FPAB / DPAK		10	A	
$I_{F(AV)}$	Average forward current $\delta = 0.5$	TO-220AB / DPAK	$T_c = 155^\circ\text{C}$	Per diode	4	A
		TO-220FPAB	$T_c = 145^\circ\text{C}$			
		TO-220AB / DPAK	$T_c = 150^\circ\text{C}$	Per device	8	A
		TO-220FPAB	$T_c = 130^\circ\text{C}$			
$I_{FSM}$	Surge non repetitive forward current		$t_p = 10$ ms Sinusoidal	50	A	
$T_{stg}$	Storage temperature range			- 65 + 175	°C	
$T_j$	Maximum operating junction temperature			175	°C	

## STTH802/CT/CB/CFP

### THERMAL PARAMETERS

Symbol	Parameter		Maximum	Unit	
R <sub>th(j-c)</sub>	Junction to case	TO-220AB / DPAK	Per diode	4.0	°C/W
		TO-220FPAB		6.5	
		TO-220AB / DPAK	Total	2.5	
		TO-220FPAB		5	
R <sub>th(j-c)</sub>	Coupling	TO-220AB / DPAK	1	°C/W	
		TO-220FPAB	3.5		

When the diodes 1 and 2 are used simultaneously:

$$\Delta T_j (\text{diode1}) = P(\text{diode1}) \times R_{th(j-c)} (\text{per diode}) + P(\text{diode2}) \times R_{th(c)}$$

### STATIC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Tests conditions		Min.	Typ.	Max.	Unit
I <sub>R</sub> *	Reverse leakage current	T <sub>j</sub> = 25°C	V <sub>R</sub> = V <sub>RRM</sub>			4	μA
		T <sub>j</sub> = 125°C			2	40	
V <sub>F</sub> **	Forward voltage drop	T <sub>j</sub> = 25°C	I <sub>F</sub> = 4 A			1.1	V
		T <sub>j</sub> = 125°C	I <sub>F</sub> = 4 A		0.81	0.95	
		T <sub>j</sub> = 25°C	I <sub>F</sub> = 8 A			1.25	
		T <sub>j</sub> = 125°C	I <sub>F</sub> = 8 A		0.95	1.1	

Pulse test: \* tp = 5ms, δ < 2%

\*\* tp = 380μs, δ < 2%


To evaluate the maximum conduction losses use the following equation :

$$P = 0.80 \times I_{F(AV)} + 0.037 I_{F(RMS)}^2$$


### DYNAMIC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Tests conditions		Min.	Typ.	Max.	Unit
trr	Reverse recovery time	T <sub>j</sub> = 25°C	I <sub>F</sub> = 0.5 A I <sub>rr</sub> = 0.25 A I <sub>R</sub> = 1A		13	20	ns
tfr	Forward recovery time	T <sub>j</sub> = 25°C	I <sub>F</sub> = 4 A dI <sub>F</sub> /dt = 100 A/μs V <sub>FR</sub> = 1.1 x V <sub>Fmax</sub>		50		ns
V <sub>FP</sub>	Forward recovery voltage	T <sub>j</sub> = 25°C	I <sub>F</sub> = 4 A dI <sub>F</sub> /dt = 100 A/μs		2.4		V


**Fig. 1:** Average forward power dissipation versus average forward current (per diode).




**Fig. 2:** Peak current versus form factor (per diode).




**Fig. 3:** Forward voltage drop versus forward current (per diode).




**Fig. 4-1:** Relative variation of thermal impedance junction to case versus pulse duration (TO-220AB, DPAK).



**Fig. 4-2:** Relative variation of thermal impedance junction to case versus duration (TO-220FPAB).



**Fig. 5-1:** Non repetitive surge peak forward current versus overload duration per diode (TO-220AB, DPAK).



**PACKAGE MECHANICAL DATA**  
TO-220FPAB

REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	4.4	4.6	0.173	0.181
B	2.5	2.7	0.098	0.106
D	2.5	2.75	0.098	0.108
E	0.45	0.70	0.018	0.027
F	0.75	1	0.030	0.039
F1	1.15	1.70	0.045	0.067
F2	1.15	1.70	0.045	0.067
G	4.95	5.20	0.195	0.205
G1	2.4	2.7	0.094	0.106
H	10	10.4	0.393	0.409
L2	16 Typ.		0.63 Typ.	
L3	28.6	30.6	1.126	1.205
L4	9.8	10.6	0.386	0.417
L5	2.9	3.6	0.114	0.142
L6	15.9	16.4	0.626	0.646
L7	9.00	9.30	0.354	0.366
Dia.	3.00	3.20	0.118	0.126

Ordering code	Marking	Package	Weight	Base qty	Delivery mode
STTH802CT	STTH802CT	TO-220AB	2.23 g	50	Tube
STTH802CB	STTH802CB	DPAK	0.3 g	75	Tube
STTH802CB-TR	STTH802CB	DPAK	0.3 g	2500	Tape & reel
STTH802CFP	STTH802CFP	TO-220FPAB	2.0 g	50	Tube

- Cooling method: by conduction (method C)
- Recommended torque value (TO-220AB): 0.8 N.m
- Maximum torque value (TO-220AB): 1.0 N.m
- Recommended torque value (TO-220FPAB): 0.55 N.m
- Maximum torque value (TO-220FPAB): 0.7 N.m
- Epoxy meets UL 94,V0