



# MBR20S100CT


## Schottky Barrier Rectifier

### Features

- Low forward voltage drop
- High frequency properties and switching speed
- Guard ring for over-voltage protection

### Applications

- Switched mode power supply
- Freewheeling diodes



### Absolute Maximum Ratings $T_a = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Value	Units
$V_{RRM}$	Maximum Repetitive Reverse Voltage	100	V
$V_R$	Maximum DC Reverse Voltage	100	V
$I_{F(AV)}$	Average Rectified Forward Current @ $T_C = 135^\circ\text{C}$	20	A
$I_{FSM}$	Non-Repetitive Peak Surge Current (per diode) 60Hz Single Half-Sine Wave	200	A
$T_J, T_{STG}$	Operating Junction and Storage Temperature	-65 to +150	$^\circ\text{C}$

### Thermal Characteristics

Symbol	Parameter	Value	Units
$R_{\theta JC}$	Maximum Thermal Resistance, Junction to Case (per diode)	1.54	$^\circ\text{C/W}$


### Electrical Characteristics $T_C = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Value	Units	
$V_{FM^*}$	Maximum Instantaneous Forward Voltage $I_F = 10\text{A}$ $I_F = 10\text{A}$ $I_F = 20\text{A}$ $I_F = 20\text{A}$	$T_C = 25^\circ\text{C}$ $T_C = 125^\circ\text{C}$ $T_C = 25^\circ\text{C}$ $T_C = 125^\circ\text{C}$	- 0.70 0.95 0.85	V V V V
$I_{RM^*}$	Maximum Instantaneous Reverse Current @ rated $V_R$	$T_C = 25^\circ\text{C}$ $T_C = 125^\circ\text{C}$	0.1 20	mA mA


\* Pulse Test: Width = 300μs, Duty Cycle = 2%

## Typical Performance Characteristics


**Figure 1. Typical Forward Voltage Characteristics (per diode)**




**Figure 2. Typical Reverse Current vs. Reverse Voltage (per diode)**



**Figure 3. Typical Junction Capacitance (per diode)**



**Figure 4. Forward Current Derating Curve**



**Figure 5. Non-Repetitive Surge Current (per diode)**

