

2SA1931


High-Current Switching Applications

- Low saturation voltage: $V_{CE(\text{sat})} = -0.4 \text{ V (max)}$
- High-speed switching time: $t_{\text{stg}} = 1.0 \mu\text{s}$ (typ.)
- Complementary to 2SC4881

Absolute Maximum Ratings ($T_c = 25^\circ\text{C}$)


Characteristic	Symbol	Rating	Unit
Collector-base voltage	V_{CEO}	-80	V
Collector-emitter voltage	V_{CEO}	-50	V
Emitter-base voltage	V_{EBO}	-7	V
Collector current	I_C	-5	A
Base current	I_B	-1	A
Collector power dissipation	P_C	2.0	W
$T_a = 25^\circ\text{C}$		20	
Junction temperature	T_J	150	$^\circ\text{C}$
Storage temperature range	T_{stg}	-65 to 150	$^\circ\text{C}$

Note: Using continuously under heavy loads (e.g. the application of high temperature/current/voltage and the significant change in



Weight: 1.7 g (typ.)

Electrical Characteristics ($T_c = 25^\circ\text{C}$)

Characteristic	Symbol	Test Conditions	Min	Typ.	Max	Unit
Collector cut-off current	I_{CEO}	$V_{CE} = -50\text{ V}, I_E = 0$	—	—	-1	μA
Emitter cut-off current	I_{EBO}	$V_{EB} = -7\text{ V}, I_C = 0$	—	—	-1	μA
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C = -10\text{ mA}, I_B = 0$	-50	—	—	V
DC current gain	h_{FE} (1)	$V_{CE} = -1\text{ V}, I_C = 1\text{ A}$	100	—	300	
	h_{FE} (2)	$V_{CE} = -1\text{ V}, I_C = 3\text{ A}$	80	—	—	
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = -2\text{ A}, I_B = -0.2\text{ A}$	—	-0.2	-0.4	V
Base-emitter saturation voltage	$V_{BE(sat)}$	$I_C = -2\text{ A}, I_B = -0.2\text{ A}$	—	-0.9	-1.5	V
Transition frequency	f_T	$V_{CE} = -1\text{ V}, I_C = -1\text{ A}$	—	80	—	MHz
Collector output capacitance	C_{ob}	$V_{CE} = -10\text{ V}, I_E = 0, f = 1\text{ MHz}$	—	100	—	pF
Switching time	Turn-on time	t_{on}	 $-I_{B1} = I_{B2} = 0.15\text{ A}$, duty cycle $\leq 1\%$	—	0.1	μs
	Storage time	t_{stg}		—	1.0	
	Fall time	t_f		—	0.1	

Marking

