

FEATURES


- Avalanche Rugged Technology
- Rugged Gate Oxide Technology
- Lower Input Capacitance
- Improved Gate Charge
- Extended Safe Operating Area
- Lower Leakage Current : 10 µA (Max.) @ $V_{DS} = 400V$
- Lower $R_{DS(ON)}$: 0.437 Ω (Typ.)

$BV_{DSS} = 400 V$

$R_{DS(on)} = 0.55 \Omega$

$I_D = 5.7 A$

TO-220F



1.Gate 2.Drain 3.Source

Absolute Maximum Ratings

Symbol	Characteristic	Value	Units
V_{DSS}	Drain-to-Source Voltage	400	V
I_D	Continuous Drain Current ($T_C=25^\circ C$)	5.7	A
	Continuous Drain Current ($T_C=100^\circ C$)	3.6	
I_{DM}	Drain Current-Pulsed	① 40	A
V_{GS}	Gate-to-Source Voltage	± 30	V
E_{AS}	Single Pulsed Avalanche Energy	② 557	mJ
I_{AR}	Avalanche Current	① 5.7	A
E_{AR}	Repetitive Avalanche Energy	① 4.4	mJ
dv/dt	Peak Diode Recovery dv/dt	③ 4.0	V/ns
P_D	Total Power Dissipation ($T_C=25^\circ C$)	44	W
	Linear Derating Factor	0.35	$W/\text{ }^\circ C$
T_J , T_{STG}	Operating Junction and Storage Temperature Range	- 55 to +150	$^\circ C$
	Maximum Lead Temp. for Soldering Purposes, 1/8" from case for 5-seconds	300	

Thermal Resistance

Symbol	Characteristic	Typ.	Max.	Units
$R_{\theta JC}$	Junction-to-Case	--	2.86	$^\circ C/W$
$R_{\theta JA}$	Junction-to-Ambient	--	62.5	

IRFS740A

N-CHANNEL
POWER MOSFET

Electrical Characteristics ($T_C=25^\circ\text{C}$ unless otherwise specified)

Symbol	Characteristic	Min.	Typ.	Max.	Units	Test Condition
BV_{DSS}	Drain-Source Breakdown Voltage	400	--	--	V	$\text{V}_{\text{GS}}=0\text{V}, \text{I}_D=250\text{ }\mu\text{A}$
$\Delta\text{BV}/\Delta T_J$	Breakdown Voltage Temp. Coeff.	--	0.50	--	$\text{V}/^\circ\text{C}$	$\text{I}_D=250\text{ }\mu\text{A}$ See Fig 7
$\text{V}_{\text{GS(th)}}$	Gate Threshold Voltage	2.0	--	4.0	V	$\text{V}_{\text{DS}}=5\text{V}, \text{I}_D=250\text{ }\mu\text{A}$
I_{GSS}	Gate-Source Leakage , Forward	--	--	100	nA	$\text{V}_{\text{GS}}=30\text{V}$
	Gate-Source Leakage , Reverse	--	--	-100		$\text{V}_{\text{GS}}=-30\text{V}$
I_{DSS}	Drain-to-Source Leakage Current	--	--	10	μA	$\text{V}_{\text{DS}}=400\text{V}$
		--	--	100		$\text{V}_{\text{DS}}=320\text{V}, \text{T}_C=125^\circ\text{C}$
$\text{R}_{\text{DS(on)}}$	Static Drain-Source On-State Resistance	--	--	0.55	Ω	$\text{V}_{\text{GS}}=10\text{V}, \text{I}_D=2.85\text{A}$ ④
g_{fs}	Forward Transconductance	--	6.21	--	Ω	$\text{V}_{\text{DS}}=50\text{V}, \text{I}_D=2.85\text{A}$ ④
C_{iss}	Input Capacitance	--	1180	1530	pF	$\text{V}_{\text{GS}}=0\text{V}, \text{V}_{\text{DS}}=25\text{V}, f=1\text{MHz}$ See Fig 5
C_{oss}	Output Capacitance	--	175	205		
C_{rss}	Reverse Transfer Capacitance	--	80	95		
$t_{\text{d(on)}}$	Turn-On Delay Time	--	18	50	ns	$\text{V}_{\text{DD}}=200\text{V}, \text{I}_D=10\text{A}, \text{R}_G=9.1\Omega$ See Fig 13 ④ ⑤
t_r	Rise Time	--	21	55		
$t_{\text{d(off)}}$	Turn-Off Delay Time	--	78	170		
t_f	Fall Time	--	28	65		
Q_g	Total Gate Charge	--	58	75	nC	$\text{V}_{\text{DS}}=320\text{V}, \text{V}_{\text{GS}}=10\text{V}, \text{I}_D=10\text{A}$ See Fig 6 & Fig 12 ④ ⑤
Q_{gs}	Gate-Source Charge	--	8.1	--		
Q_{gd}	Gate-Drain("Miller") Charge	--	31.3	--		

Source-Drain Diode Ratings and Characteristics

Symbol	Characteristic	Min.	Typ.	Max.	Units	Test Condition
I_S	Continuous Source Current	--	--	5.7	A	Integral reverse pn-diode in the MOSFET
I_{SM}	Pulsed-Source Current ①	--	--	40		
V_{SD}	Diode Forward Voltage ④	--	--	1.5	V	$\text{T}_J=25^\circ\text{C}, \text{I}_S=5.7\text{A}, \text{V}_{\text{GS}}=0\text{V}$
t_{rr}	Reverse Recovery Time	--	315	--	ns	$\text{T}_J=25^\circ\text{C}, \text{I}_F=10\text{A}$ $d\text{I}_F/dt=100\text{A}/\mu\text{s}$ ④
Q_{rr}	Reverse Recovery Charge	--	2.84	--		

Notes :

- ① Repetitive Rating : Pulse Width Limited by Maximum Junction Temperature
- ② $L=30\text{mH}, \text{I}_{\text{AS}}=5.7\text{A}, \text{V}_{\text{DD}}=50\text{V}, \text{R}_G=27\Omega$, Starting $\text{T}_J=25^\circ\text{C}$
- ③ $\text{I}_{\text{SD}} \leq 10\text{A}, d\text{I}/dt \leq 170\text{A}/\mu\text{s}, \text{V}_{\text{DD}} \leq \text{BV}_{\text{DSS}}$, Starting $\text{T}_J=25^\circ\text{C}$
- ④ Pulse Test : Pulse Width = $250\text{ }\mu\text{s}$, Duty Cycle $\leq 2\%$
- ⑤ Essentially Independent of Operating Temperature