ISL9N310AP3/ISL9N310AS3ST/ISL9N310AS3

N-Channel Logic Level PWM Optimized UltraFET® Trench Power MOSFETs

General Description

This device employs a new advanced trench MOSFET technology and features low gate charge while maintaining low on-resistance.

Optimized for switching applications, this device improves the overall efficiency of DC/DC converters and allows operation to higher switching frequencies.

Applications

- DC/DC converters

Features

- Fast switching
- $r_{DS(ON)}$ = 0.008Ω (Typ), V_{GS} = 10V
- $r_{DS(ON)}$ = 0.0115Ω (Typ), V_{GS} = 4.5V
- Q_g (Typ) = 17nC, V_{GS} = 5V
- Q_{gd} (Typ) = 5.4nC
- C_{ISS} (Typ) = 1800pF



TO-263AB



TO-262AA



TO-220AB

MOSFET Maximum Ratings T_A = 25°C unless otherwise noted

Symbol	Parameter	Ratings	Units
V_{DSS}	Drain to Source Voltage	30	V
V_{GS}	Gate to Source Voltage	±20	V
I_D	Drain Current		
	Continuous (T_C = 25°C, V_{GS} = 10V)	62	A
	Continuous (T_C = 100°C, V_{GS} = 4.5V)	36	A
	Continuous (T_C = 25°C, V_{GS} = 10V, $R_{\theta JA}$ = 43°C/W)	13.5	A
	Pulsed	Figure 4	A
P_D	Power dissipation	70	W
	Derate above 25°C	0.47	W/°C
T_J, T_{STG}	Operating and Storage Temperature	-55 to 175	°C

Thermal Characteristics

$R_{\theta JC}$	Thermal Resistance Junction to Case TO-220, TO-262, TO-263	2.14	°C/W
$R_{\theta JA}$	Thermal Resistance Junction to Ambient TO-220, TO-262, TO-263	62	°C/W
$R_{\theta JA}$	Thermal Resistance Junction to Ambient TO-263, 1in^2 copper pad area	43	°C/W

Package Marking and Ordering Information

Device Marking	Device	Package	Reel Size	Tape Width	Quantity
N310AS	ISL9N310AS3ST	TO-263AB	330mm	24mm	800 units
N310AS	ISL9N310AS3	TO-262AA	Tube	N/A	50
N310AP	ISL9N310AP3	TO-220AB	Tube	N/A	50

Electrical Characteristics T_A = 25°C unless otherwise noted

Symbol	Parameter	Test Conditions		Min	Typ	Max	Units
Off Characteristics							
B_{VDSS}	Drain to Source Breakdown Voltage	I_D = 250μA, V_{GS} = 0V		30	-	-	V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS} = 25V		-	-	1	μA
		V_{GS} = 0V	T_C = 150°C	-	-	250	
I_{GSS}	Gate to Source Leakage Current	V_{GS} = ±20V		-	-	±100	nA
On Characteristics							
$V_{GS(TH)}$	Gate to Source Threshold Voltage	V_{GS} = V_{DS}, I_D = 250μA		1	-	3	V
$r_{DS(ON)}$	Drain to Source On Resistance	I_D = 62A, V_{GS} = 10V		-	0.008	0.010	Ω
		I_D = 36A, V_{GS} = 4.5V		-	0.0115	0.015	
Dynamic Characteristics							
C_{ISS}	Input Capacitance	V_{DS} = 15V, V_{GS} = 0V, f = 1MHz		-	1800	-	pF
C_{OSS}	Output Capacitance			-	390	-	pF
C_{RSS}	Reverse Transfer Capacitance			-	190	-	pF
$Q_{g(TOT)}$	Total Gate Charge at 10V	V_{GS} = 0V to 10V	V_{DD} = 15V, I_D = 36A, I_g = 1.0mA		32	48	nC
$Q_{g(5)}$	Total Gate Charge at 5V	V_{GS} = 0V to 5V		-	17	26	nC
$Q_{g(TH)}$	Threshold Gate Charge	V_{GS} = 0V to 1V		-	1.9	2.9	nC
Q_{gs}	Gate to Source Gate Charge			-	3.7	-	nC
Q_{gd}	Gate to Drain “Miller” Charge			-	5.4	-	nC
Switching Characteristics (V_{GS} = 4.5V)							
t_{ON}	Turn-On Time	V_{DD} = 15V, I_D = 13.5A, V_{GS} = 4.5V, R_{GS} = 9.1Ω		-	-	95	ns
$t_{d(ON)}$	Turn-On Delay Time			-	11	-	ns
t_r	Rise Time			-	52	-	ns
$t_{d(OFF)}$	Turn-Off Delay Time			-	39	-	ns
t_f	Fall Time			-	36	-	ns
t_{OFF}	Turn-Off Time			-	-	112	ns
Switching Characteristics (V_{GS} = 10V)							
t_{ON}	Turn-On Time	V_{DD} = 15V, I_D = 13.5A, V_{GS} = 10V, R_{GS} = 12Ω		-	-	68	ns
$t_{d(ON)}$	Turn-On Delay Time			-	7	-	ns
t_r	Rise Time			-	38	-	ns
$t_{d(OFF)}$	Turn-Off Delay Time			-	78	-	ns
t_f	Fall Time			-	44	-	ns
t_{OFF}	Turn-Off Time			-	-	183	ns
Unclamped Inductive Switching							
t_{AV}	Avalanche Time	I_D = 3.0A, L = 3.0mH		200	-	-	μs
Drain-Source Diode Characteristics							
V_{SD}	Source to Drain Diode Voltage	I_{SD} = 36A		-	-	1.25	V
		I_{SD} = 20A		-	-	1.0	V
t_{rr}	Reverse Recovery Time	I_{SD} = 36A, dI_{SD}/dt = 100A/μs		-	-	29	ns
Q_{RR}	Reverse Recovered Charge	I_{SD} = 36A, dI_{SD}/dt = 100A/μs		-	-	21	nC

Typical Characteristic



Figure 1. Normalized Power Dissipation vs Ambient Temperature



Figure 2. Maximum Continuous Drain Current vs Case Temperature



Figure 3. Normalized Maximum Transient Thermal Impedance



Figure 4. Peak Current Capability