



NDP6060L / NDB6060L


N-Channel Logic Level Enhancement Mode Field Effect Transistor

General Description


These logic level N-Channel enhancement mode power field effect transistors are produced using Fairchild's proprietary, high cell density, DMOS technology. This very high density process has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulses in the avalanche and commutation modes. These devices are particularly suited for low voltage applications such as automotive, DC/DC converters, PWM motor controls, and other battery powered circuits where fast switching, low in-line power loss, and resistance to transients are needed.

Features


- 48A, 60V. $R_{DS(ON)} = 0.025\Omega$ @ $V_{GS} = 5V$.
- Low drive requirements allowing operation directly from logic drivers. $V_{GS(TH)} < 2.0V$.
- Critical DC electrical parameters specified at elevated temperature.
- Rugged internal source-drain diode can eliminate the need for an external Zener diode transient suppressor.
- 175°C maximum junction temperature rating.
- High density cell design for extremely low $R_{DS(ON)}$.
- TO-220 and TO-263 (D²PAK) package for both through hole and surface mount applications.



TO-220
NDP Series



TO-263AB
NDB Series



Absolute Maximum Ratings

$T_c = 25^\circ C$ unless otherwise noted

Symbol	Parameter	NDP6060L	NDB6060L	Units
V_{DSS}	Drain-Source Voltage	60		V
V_{DGR}	Drain-Gate Voltage ($R_{GS} \leq 1 M\Omega$)	60		V
V_{GSS}	Gate-Source Voltage - Continuous	± 16		V
	- Nonrepetitive ($t_p < 50 \mu s$)	± 25		
I_D	Drain Current - Continuous	48		A
	- Pulsed	144		
P_D	Total Power Dissipation @ $T_c = 25^\circ C$	100		W
	Derate above $25^\circ C$	0.67		
T_J, T_{STG}	Operating and Storage Temperature	-65 to 175		°C
T_L	Maximum lead temperature for soldering purposes, 1/8" from case for 5 seconds	275		°C

Electrical Characteristics ($T_c = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
DRAIN-SOURCE AVALANCHE RATINGS (Note 1)						
W_{DSS}	Single Pulse Drain-Source Avalanche Energy	$V_{DD} = 25 \text{ V}$, $I_D = 48 \text{ A}$			200	mJ
I_{AR}	Maximum Drain-Source Avalanche Current				48	A
OFF CHARACTERISTICS						
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS} = 0 \text{ V}$, $I_D = 250 \mu\text{A}$	60			V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS} = 60 \text{ V}$, $V_{GS} = 0 \text{ V}$			250	μA
		$T_J = 125^\circ\text{C}$			1	mA
I_{GSSF}	Gate - Body Leakage, Forward	$V_{GS} = 16 \text{ V}$, $V_{DS} = 0 \text{ V}$			100	nA
I_{GSSR}	Gate - Body Leakage, Reverse	$V_{GS} = -16 \text{ V}$, $V_{DS} = 0 \text{ V}$			-100	nA
ON CHARACTERISTICS (Note 1)						
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}$, $I_D = 250 \mu\text{A}$	1		2	V
		$T_J = 125^\circ\text{C}$	0.65		1.5	
$R_{DS(on)}$	Static Drain-Source On-Resistance	$V_{GS} = 5 \text{ V}$, $I_D = 24 \text{ A}$			0.025	Ω
		$T_J = 125^\circ\text{C}$			0.04	
		$V_{GS} = 10 \text{ V}$, $I_D = 24 \text{ A}$			0.02	
$I_{D(on)}$	On-State Drain Current	$V_{GS} = 5 \text{ V}$, $V_{DS} = 10 \text{ V}$	48			A
g_{FS}	Forward Transconductance	$V_{DS} = 10 \text{ V}$, $I_D = 24 \text{ A}$	10			S
DYNAMIC CHARACTERISTICS						
C_{iss}	Input Capacitance	$V_{DS} = 25 \text{ V}$, $V_{GS} = 0 \text{ V}$, $f = 1.0 \text{ MHz}$			1630	pF
C_{oss}	Output Capacitance				460	pF
C_{rss}	Reverse Transfer Capacitance				150	pF
SWITCHING CHARACTERISTICS (Note 1)						
$t_{D(on)}$	Turn - On Delay Time	$V_{DD} = 30 \text{ V}$, $I_D = 48 \text{ A}$, $V_{GS} = 5 \text{ V}$, $R_{GEN} = 15 \Omega$, $R_{GS} = 15 \Omega$			15	nS
t_r	Turn - On Rise Time				320	nS
$t_{D(off)}$	Turn - Off Delay Time				49	nS
t_f	Turn - Off Fall Time				161	nS
Q_g	Total Gate Charge	$V_{DS} = 48 \text{ V}$, $I_D = 48 \text{ A}$, $V_{GS} = 5 \text{ V}$			36	nC
Q_{gs}	Gate-Source Charge				8.2	nC
Q_{gd}	Gate-Drain Charge				21	nC

Electrical Characteristics ($T_c = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
DRAIN-SOURCE DIODE CHARACTERISTICS						
I_s	Maximum Continuous Drain-Source Diode Forward Current				48	A
I_{SM}	Maximum Pulsed Drain-Source Diode Forward Current				144	A
V_{SD}	Drain-Source Diode Forward Voltage	$V_{GS} = 0 \text{ V}, I_s = 24 \text{ A}$ (Note 1)			1.3	V
			$T_j = 125^\circ\text{C}$		1.2	
t_{rr}	Reverse Recovery Time	$V_{GS} = 0 \text{ V}, I_F = 48 \text{ A},$ $dI_F/dt = 100 \text{ A}/\mu\text{s}$	35	75	140	ns
I_{rr}	Reverse Recovery Current		2	3.6	8	A
THERMAL CHARACTERISTICS						
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case				1.5	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient				62.5	°C/W

Note:

1. Pulse Test: Pulse Width $\leq 300 \mu\text{s}$, Duty Cycle $\leq 2.0\%$.

Typical Electrical Characteristics




Figure 1. On-Region Characteristics.




Figure 2. On-Resistance Variation with Gate Voltage and Drain Current.




Figure 3. On-Resistance Variation with Temperature.




Figure 4. On-Resistance Variation with Drain Current and Temperature.




Figure 5. Transfer Characteristics.




Figure 6. Gate Threshold Variation with Temperature.

Typical Electrical Characteristics (continued)




Figure 7. Breakdown Voltage Variation with Temperature.




Figure 8. Body Diode Forward Voltage Variation with Current and Temperature.




Figure 9. Capacitance Characteristics.




Figure 10. Gate Charge Characteristics.




Figure 11. Switching Test Circuit.




Figure 12. Switching Waveforms.

Typical Electrical Characteristics (continued)




Figure 13. Transconductance Variation with Drain Current, and Temperature




Figure 14. Maximum Safe Operating Area




Figure 15. Transient Thermal Response Curve.